

Prozone Water Products Commercial Systems

PZ2-16 Commercial Systems

The PZ2-16 for up to 200,000 gallons (750,000 liters) is a compressor driven ozone system which can inject ozone under almost any hydraulic condition. The system is built with commercial grade compressors, solid state power supplies, our patented advanced Hybrid ozone generators, and muffling to ensure quiet operation.



Upgrade Optional
Skid Mount Includes:

- Full Turnkey Water In
Water Out Installation
- Water Circulation Pump
- Counter Flow Contacting
- Static Mixer
- Degas Column

Additional Upgrade Options:

- ORP/ph Monitoring
- Ozone Destruct
- Ozone Monitoring
- Below Water Solenoid Kit



T-O₃ NATURAL TECHNOLOGY

Reduces Chemical Usage, Improves Sanitation, Eliminates Odors, Produces Crystal Clear Water

No recurring maintenance or special skills are required. All PZ2 residential and commercial systems carry a two-year warranty; Contact a Prozone engineer for further engineering options on the PZ2 Series.

Electrical System Options

- 110/220 VAC, 60 hz
- 220/240 VAC, 60 hz
- 230 VAC, 50 hz
- Universal Solid State Inverter Ballast: 90 VAC to 270 VAC

Installation Kit to Met NSF Std. 50 Available

- Kit includes NEMA housing, contacting system, and degassing column; boost pump optional

Specifications

- Arc Life (Nominal): 20,000 Hours
- Compressor Life: (Nominal): 40,000 Hours
- Operating Temperature: -25° F. to +140° F.
- Storage Temperature: -60° F. to +160° F.



Front of PZ2-16 on
Optional Skid Mount
Upgrade



Back of PZ2-16
on Optional Skid
Mount Upgrade



Environmentally Friendly



Commercial Pool Sizing	
Nominal	400,000
Loaded	200,000
Dimensions of PZ2-16	
24" X 7" X 50"	
Weight without skid	
107 lbs	
Dimensions of PZ2-16 with Skid Mounts	
42" X 37" X 60"	

