

# Prozone Water Products Commercial Systems

## PZ2-36 Commercial Systems

The PZ2-36 for treatment up to 450,000 gallons (1.7 million liters) is a compressor driven ozone system which can inject ozone under almost any hydraulic condition. The system is built with commercial grade compressors, solid state power supplies, our patented advanced Hybrid ozone generators, and muffling to ensure quiet operation.

PZ2-36 - Front view



### T-O3 NATURAL TECHNOLOGY

Reduces Chemical Usage, Improves Sanitation, Eliminates Odors, Produces Crystal Clear Water

No recurring maintenance or special skills are required. All PZ2 residential and commercial systems carry a two-year warranty; Contact a Prozone engineer for further engineering options on the PZ2 Series.

### Electrical System Options

- 110/220 VAC, 60 hz
- 220/240 VAC, 60 hz
- 230 VAC, 50 hz
- Universal Solid State Inverter Ballast: 90 VAC to 270 VAC

### Installation Kit to Met NSF Std. 50 Available

- Kit includes NEMA housing, contacting system, and degassing column; boost pump optional

### Specifications

- Arc Life (Nominal): 20,000 Hours
- Compressor Life: (Nominal): 40,000 Hours
- Operating Temperature: -25° F. to +140° F.
- Storage Temperature: -60° F. to +160° F.



PZ2-36 - Rear view

### Skid Mount Includes:

- Full Turnkey Water In  
Water Out Installation
- Water Circulation Pump
- Counter Flow Contacting
- Static Mixer
- Degas Column

### Additional Upgrade Options:

- Orp/ph Monitoring
- Ozone Destruct
- Ozone Monitoring
- Below Water Solenoid Kit



### Commercial Pool Sizing

Nominal	900,000
Loaded	450,000

### Dimensions of PZ2-24 with Skid Mounts

48" X 37" X 60"

